

Panther 6" Seamless Rollformer

Standard Equipment

- Front pull guillotine
- Seven station aluminum box
- Emergency shutdown switch
- Easy adjust entrance guides
- Two quick release runout stands

2 Year Warranty Parts & Labor

Standard Upright System

- 2 spool upright & 2 aluminum spools
- New aluminum spools less than half the weight of steel spools
- Weight distributing upright system distributes the weight of the coils to the floor of the vehicle, not the machine



Front pull guillotine



KWMGutterman

795 South Larkin Avenue
Rockdale, Illinois 60436

Phone (815) 725-9205 Fax (815) 725-4429
E-mail panther@kwmgutterman.com
www.kwmgutterman.com

Specifications

Dimensions

Top of spools to the bottom of machine 52". 25" Wide. Length 127" with straight blade guillotine. 129 3/4" with front pull guillotine.

Construction

3/8" steel frame welded on a jig fixture for accuracy. Fully enclosed with 7 gauge steel sides. All parts individually painted prior to assembly.

Drive/Forming Rollers

Fourteen drive forming rollers—8 bottom, 6 top. Rollers are 10-18 steel plated, .002 industrial hard-chrome.

Weight

1,690 lbs.

Power

3/4 HP, high torque sealed motor. 1 HP reduction gear. Machine plugs directly into 110-120V outlet.

Production

Approximately 35 feet per minute

Recommended Materials

Material	Maximum Gauge
Aluminum	.032
Painted steel	26
Galvanized steel	26
Copper	16 oz.³⁄₄ hard

Options

- Straight blade guillotine
- Additional runout support stands
- 220 volt/50hz.
- Single, double or triple spool upright available
- Machine mount cradle